## **ErP Information**

| Fan Types                              | Axial fan                             |  |  |
|--|---------------------------------------|--|--|
| Directive (or Standard) for Regulation |                                       | ErP Directive 2009/125/EC COMMISSION REGULATION (EU) No 327/2011 |  |
| Model Name                             | WZDK170-38G-1+ZL-<br>560*169*15*4(ZJ) | Rev.   |  |
| Prepare by                             |                                       |  |  |

## Specified Information of Fan:

| No.  | Information Item  | Comment   |
|------|---|---|
| 1    | η <sub>target</sub> =   | 29.7%   |
| 2    | Overall efficiency (η <sub>e</sub> ) =  | 32.2%   |
| 3    | Pass or not (Criteria: η <sub>e</sub> ≧η <sub>target</sub> )  | Pass  |
| 4    | Measurement category (A-D)  | Α   |
| 5    | Efficiency category (static or total)   | Static  |
| 6    | Efficiency grade at optimum energy efficiency point   | N =40   |
| 7    | VSD is integrated within the fan  | YES   |
| 8    | Year of Manufacture   | 2016  |
| 9    | Manufacturer's name and place of manufacture  | Bosch Thermotechnik GmbH<br>Junkersstraße 20-24, 73249<br>Wernau, Germany |
| 10.1 | Rated motor power input(s) (kW), at optimum energy efficiency   | 0.232 kW  |
| 10.2 | Rated motor flow rate(s) at optimum energy efficiency   | 1.314 m <sup>3</sup> /s   |
| 10.3 | Rated motor pressure(s) at optimum energy efficiency  | 50 Pa   |
| 11   | Rotations per minute (R.P.M)at the optimum energy efficiency point  | 850r/min  |
| 12   | Specific ratio  | 1.001   |
| 13   | Information relevant for facilitating disassembly, recycling or disposal at end-of-life   | all materials can be recycled   |
| 14   | Information relevant to minimize impact on the environment and ensure optimal life expectancy as regards installation, use and maintenance of the fan                             | For installation, the clearance of 500 mm shall be kept from inlet        |
| 15   | Description of additional items used when determining the fan energy efficiency, such as ducts, that are not described in the measurement category and not supplied with the fan. | Measurement category A, fan is free inlet and outlet conditions           |
| 16   | Motor manufacturer  | NIDEC SHIBAURA(ZHEJIANG)<br>CORP.   |